## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI011200-R4

DATE: 07/24/2012

CERTIFICATION PROGRAM: <u>Fire</u>

COMPANY: Orepac

CODE: <u>1234-1</u>

**EXPIRATION DATE:** <u>07/31/2026</u>

**REVISION DATE:** <u>04/11/2024</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Orepac Building Products, Inc.	20 Minute Fiberglass Reinforced Faced
30160 SW Orepac Avenue	Door w/Proprietary Core
Wilsonville, OR 97070	(Simulated Panel Type or Flush)
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	Single Door Maximum Size: 3'0" x 6'8" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2008) UL 10C (2009) CAN4 S104 (1985)	20 Minute-Positive Pressure With Hose Stream Category A - No Additional Edge Sealing
	Required

## **TEST REPORT**

Intertek Test Report No: J20051379-231, 3084465, 317611MID-002, 3187023MID-002 & 10035435MID-001



Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com

NOPC-03/30/2023