

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI011353-R4
DATE: 12/11/2012
CERTIFICATION PROGRAM: Fire
COMPANY: Orepac
CODE: 1234-1
EXPIRATION DATE: 12/31/2024
REVISION DATE: 02/28/2023

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Orepac Building Products, Inc. 30160 SW Orepac Avenue Wilsonville, OR 97070	20 Minute Neutral Pressure Fire Door Assemblies w/ Hose Stream Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations 1/2" Minimum Latch Throw Single or Double Swing Only Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999) UL 10B (2009) UBC Standard 7-2 (1997)	20 Minute-Neutral Pressure With Hose Stream

TEST REPORT
Intertek Test Report No: AU10124008-1, 3059877, J20012862-23, 3025659, 3137713COQ-007, 3151140COQ-004, 3168294MID-004b, 3004902, 3175675MID-004, 3058118-03, 3058118-02, 3187023MID-001, 3042535-1, 3042535-2, 3192291COQ-005, 3108034COQ-003/101417745COQ-003a Warnock-Hershey Report No: WHI-495-1525, WHI-495-1197, WHI-495-0897

Administrator's Signature:  _____

**NATIONAL ACCREDITATION AND
MANAGEMENT INSTITUTE, INC.**
4794 George Washington Memorial Highway
Hayes, VA 23072
Tel: (804) 684-5124/nami@namiinc.com