NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI011913-R1

DATE: <u>03/24/2014</u>

CERTIFICATION PROGRAM: Fire

COMPANY: Artistic

CODE: <u>1992-1</u>

REVISION DATE: <u>08/31/2020</u> EXPIRATION DATE: <u>03/31/2021</u>

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION 90 Minute Glazed Composite Stile & Rail		
Artistic Doors and Windows			
Manufacturing, LLC	Fire Door Assembly w/Composite Frame		
10 South Inman Avenue	Manufacturer Specific Fire Doors for Single Swing Installation in 90 Minute Locations		
Avenel, NJ 07001	1/2" Minimum Latch Throw Single Swing Only Glazing: 3/16" Firelite		
	Single Door Maximum Size: 3'6" x 6'8" Minimum Thickness: 1-3/4" Glazing Maximum Size: 2'1" x 5'8"		

	PRODUCT RATING		
NFPA 252 (1999) UL 10C (1998) UBC Standard 7-2 (1997)	90 Minute-Positive Pressure w/Hose Stream Category B Door-Additional Edge Seal Required For Use With Proprietary Composite Frame (or may also be installed in Category C-Frame in accordance with individual manufacturer's listing)		

TEST REPORT

Intertek Test Report No.: 3060406 Intertek Engineering Evaluation No.: 3064606

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124 Fax: (804) 684-5122