NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI012832-R2

DATE: 09/08/2015

CERTIFICATION PROGRAM: Fire

COMPANY: <u>Lumbermen</u>

CODE: 1021-1

REVISION DATE: <u>06/22/2023</u> EXPIRATION DATE: <u>09/30/2026</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION |
|---------------------------------|---|
| Lumbermen's Incorporated | 20 Minute Fiberglass Reinforced Faced |
| 3810 Roger B. Chaffee Drive, SE | Door w/Proprietary Core |
| Grand Rapids, MI 49548 | (Simulated Panel Type or Flush) |
| | Manufacture Specific Fire Door Frames for Single Swing Installation in 20 Minute Locations |
| | Single Door Maximum Size: 3'0" x 6'8" |
| | Minimum Thickness: 1-3/4" |

| SPECIFICATION | PRODUCT RATING |
|--|--|
| UL 10C (2009) NFPA 252 (2008) CAN4 S104 (1985) | 20 Minute-with Hose Stream Positive Pressure Category A- No Additional Edge Sealing Required |
| TEST REPORT | |

Intertek Test Report No: J20051379-231, 3084465, 317611MID-002, 3187023MID-002, & 10035435MID-001

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5122