NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI012913-R3

DATE: 10/19/2015

CERTIFICATION PROGRAM: <u>Fire</u>

COMPANY: Dyke Industries

CODE: 452-1

REVISION DATE: <u>11/14/2023</u> EXPIRATION DATE: <u>10/31/2028</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Dyke Industries	90 Minute Positive Pressure Fire Door
10500 Northwest 95th Avenue	Assemblies w/o Hose Stream
Medley, FL 33178	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 90 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 3'0" x 8'0" Maximum Size: 3'6" x 7'0"
	Maximum Size: 6'0" x 7'0" Minimum Thickness: 1-11/16"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2008)/UL 10B (2009)/ UL 10C (2009/UBC 7-2 (1997) CAN ULC S104 (2010)	90 Minute-Positive Pressure Without Hose Stream Category B - Additional Edge Sealing System Required

TEST REPORT

Intertek Test Report No: 100108677COQ-001, 100211525COQ-001, 100754937MID-001, J20012862-231, 3150506MID-004, 3025659



Administrator's Signature:_

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Tel: (804) 684-5124 nami@namiinc.com