NOTICE OF PRODUCT CERTIFICATION

DES ACCREDITED	CERTIFICATION NO:	NI013447-R5
S ONNI ACCREDIT	DATE:	<u>12/12/2016</u>
No los	CERTIFICATION PROGRAM:	Fire
NAMI	COMPANY:	BMC Millwork
(RI CAS) A	CODE:	1665-1
Thackment INSTITU	REVISION DATE:	<u>06/29/2023</u>
CERTIFIED PRODUCT	EXPIRATION DATE:	<u>12/31/2023</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
BMC Millwork Corporation	20 Minute Positive Pressure	
399 Northpoint Parkway	Flush or Molded Interior Side-Hinged	
Acworth, GA 30102	Door w/Wheatboard Core	
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations	
	1/2" Minimum Latch Throw Single Swing Only	
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"	

SPECIFICATION

NFPA 252 (1999) UL 10(b) (1997/2009) CAN4-S104 (1985) UBC Standard 7-2 (1994/1997) UL 10(c) (2009) PRODUCT RATING

20 Minute-Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3137714COQ-008

ShO

Administrator's Signature:

NATIONAL ACCREDITATION AND **MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124 nami@namiinc.com