# **NOTICE OF PRODUCT CERTIFICATION**



This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com.</u> NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Monterey Bay Door, Inc.	Plastpro's 20 Minute Neutral Pressure Fire
755 Vertin Avenue, Suite F	Door Assemblies w/o Hose Stream
Salinas, CA 93901	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

### SPECIFICATION

#### **PRODUCT RATING**

NFPA 252 (1999) UL 10B (2009) UBC Standard 7-2 (1997) 20 Minute-Neutral Pressure Without Hose Stream

#### **TEST REPORT**

Intertek Test Report No: 3182549MID-005, 100644112MID-002, 100644112MID-004, 3166995MID-006, 3178456MID-003, 3182549MID-005b, 100359215MID-010b, 100359215MID-010c

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com