

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI013670-R5
DATE: 03/30/2017
CERTIFICATION PROGRAM: Fire
COMPANY: 84 Lumber
CODE: 2201-1
REVISION DATE: 01/29/2024
EXPIRATION DATE: 03/31/2033

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
84 Lumber, Inc. 4287 Stough Road Concord, NC 28207	<p style="text-align: center;">20 Minute Positive & Neutral Pressure</p> <p style="text-align: center;">Flush or Molded Interior Side-Hinged</p> <p style="text-align: center;">Door w/Particleboard Core</p> <p style="text-align: center;">Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations</p> <p style="text-align: center;">1/2" Minimum Latch Throw Single Swing Only</p> <p style="text-align: center;">Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"</p>

SPECIFICATION	PRODUCT RATING
<p style="text-align: center;">NFPA 252 (1999) UL 10(b) (2009) ASTM E2074 (2000) CAN4-S104(ULC S104) UBC Standard 7-2 (1994/1997) UL 10(c) (1998)</p>	<p style="text-align: center;">20 Minute-Neutral/Positive Pressure With Hose Stream</p> <p style="text-align: center;">Category B Door-Additional Edge Seal Required</p> <p style="text-align: center;">For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)</p>

TEST REPORT
Intertek Test Report No: 3137713COQ-007

Administrator's Signature: _____

NATIONAL ACCREDITATION AND
MANAGEMENT INSTITUTE, INC.
 4794 George Washington Memorial Highway
 Hayes, VA 23072
 Tel: (804) 684-5124
nami@namiinc.com