## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI013671-R5

**DATE:** 04/03/2017

**CERTIFICATION PROGRAM:** Fire

COMPANY: 84 Lumber

**CODE:** 2201-1

REVISION DATE: 01/29/2024

**EXPIRATION DATE:** 04/30/2033

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION		
84 Lumber, Inc.	Jeld Wen Premium 20 Minute Neutral		
4287 Stough Road	Pressure Fiberglass Side-Hinged Door		
Concord, NC 28207	Assemblies		
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations		
	1/2" Minimum Latch Throw Single Swing and Pairs Allowed		
	Single Swing Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"		
	Pairs Maximum Size: 6'0" x 6'8" Minimum Thickness: 1-3/4"		

SPECIFICATION	PRODUCT RATING		
NFPA 252 (2008) UL 10B (2008/2009) CAN/ULC S104 (2010)	20 Minute-Neutral Pressure With Hose Stream Category B - Additional Edge Sealing Required		
TEST REPORT			

Intertek Test Report No: 3091617, 3145981MID-005b, 3153159MID-007, 100211525COQ-001

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com