NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI013673-R5

DATE: 04/03/2017

CERTIFICATION PROGRAM: Fire

COMPANY: 84 Lumber

CODE: 2201-1

REVISION DATE: 01/29/2024

EXPIRATION DATE: <u>04/30/2033</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
84 Lumber, Inc.	20 Minute Neutral Pressure Fire Door
4287 Stough Road	Assemblies w/o Hose Stream
Concord, NC 28207	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999)	20 Minute-Neutral Pressure
UL 10B (2009)	Without Hose Stream
UBC Standard 7-2 (1997)	

TEST REPORT

Intertek Test Report No: 3073067, 3043898, 307008-1, 100108677COQ-001, 3059877, J20012862-23, 3025659, 3192291COQ-005, 3048495, 3108034COQ-003, Warnock-Hershey Test Report No: WHI-495-1685, WHI-495-1197, WHI-495-0897

Shie

Administrator's Signature: ___

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com

NOPC-03/30/2023