
## NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI013753-R1

**DATE:** 06/14/2017

CERTIFICATION PROGRAM: <u>Fire</u>

**COMPANY:** <u>Harvey</u>

**CODE:** 310-1

REVISION DATE: <u>12/09/2021</u> EXPIRATION DATE: <u>06/30/2031</u>

To verify that the "Notice of Product Certification" is valid, please visit <a href="www.NAMICertification.com">www.NAMICertification.com</a> to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Harvey Building Products	20 Minute Positive Pressure Steel Fire
30 Jack's Bridge Road	Door Assemblies w/o Hose Stream
Londonderry, NH 03053	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 7'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999) UL 10C (1998) UL 10B (1997) UBC Standard 7-2 (1997)	20 Minute-Positive Pressure Without Hose Stream Category B Door-Additional Edge Seal Required (unless specified in individual manufacturer's listing) For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)
Intertek Test Rep	ST REPORT  oort No: 3042535-1, 3042535-2  iver of Retest: W-1653

110

Administrator's Signature: \_\_

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com