## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO: NI013963-R2** 

**DATE:** 02/08/2018

CERTIFICATION PROGRAM: Fire

**COMPANY:** Gem State

**CODE:** 2403-1

**REVISION DATE:** <u>03/12/2024</u> **EXPIRATION DATE:** <u>02/28/2026</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="https://www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Gem State Doors & Millwork	Lynden 20 Minute L20SP
608 Carnation Drive	Wood Core Fire Door Assembly
Nampa, Idaho 83653	Manufacturer Specific Fire Doors for Single and Double Swing Installation in 20 Minute Locations  1/2" Minimum Latch Throw for Singles 3/4" Minimum Latch Throw for Double Single & Double Swing Only
	Single Maximum Size: 4'0" x 9'0" Single Maximum Size: 3'6" x 10'0" Double Maximum Size: 8'0" x 9'0" Double Egress Maximum Size: 8'0" x 8'0" Dutch Door: 4'0" x 8'0" Door w/Transom Maximum Size: 4'0" x 10'0" Transom Maximum Size: 3'0" x 3'4" Minimum Thickness: 1-3/4"

NITID 4 0.50 (0.000) (0.010)	PRODUCT RATING
UBC Standard 7-2 (1994)(1997)(2015)	20 Minute-Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required (unless specified in individual manufacturer's listing) For Use in Category C-Standard Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

## **TEST REPORT**

Intertek Test Report No: 491-7972/3052139/3060684/3075954/3157236/103140421

Administrator's Signature: \_\_\_\_



## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124 nami@namiinc.com

NOPC 03/30/2023