NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014072-R1

> 05/22/2018 DATE:

CERTIFICATION PROGRAM: Fire

> Mac-Vann, Inc. **COMPANY:**

> > CODE: 2014-1

REVISION DATE: 02/14/2022 05/31/2026 **EXPIRATION DATE:**

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim Please review and advise NAMI if any corrections are required to this document. certification status.

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION | |
|--------------------------|---|--|
| Mac-Vann, Inc. | 20 Minute Positive & Neutral Pressure | |
| 4792 Rawls Church Road | Flush or Molded Interior Side-Hinged | |
| Fuquay-Varina, NC 27526 | Door w/Particleboard Core | |
| | Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations | |
| | 1/2" Minimum Latch Throw Single Swing Only | |
| | Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4" | |

| SPECIFICATION | PRODUCT RATING |
|---|---|
| NFPA 252 (1999) | 20 Minute-Neutral/Positive Pressure |
| UL 10(b) (2009) | With Hose Stream |
| ASTM E2074 (2000) | Category B Door-Additional Edge Seal |
| CAN4-S104(ULC S104) | Required |
| UBC Standard 7-2 (1994/1997) UL 10(c) (1998) | For Use in Category C Frame |
| | (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing) |

| TEST REPORT | |
|---|--|
| Intertek Test Report No: 3137713COO-007 | |

Administrator's Signature: _

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway **Hayes, VA 23072** Tel: (804) 684-5124

nami@namiinc.com