## **NOTICE OF PRODUCT CERTIFICATION**



This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS       | PRODUCT DESCRIPTION  |
|--------------------------------|--|
| Orepac Building Products, Inc. | Woodgrain 20 Minute Category C   |
| 30160 SW Orepac Avenue         | <b>Proprietary Wood Door Frames</b>  |
| Wilsonville, OR 97070          |  |
|                                | Manufacture Specific Fire Door Frames for Single and<br>Double Swing Installation in 20 Minute Locations |
|                                | Single Door Maximum Size: 4'0" x 9'0"<br>Double Door Maximum Size: 8'0" x 9'0"                           |
|                                | Minimum Thickness: 3-3/4"  |

| SPECIFICATION   | PRODUCT RATING   |
|---|--|
| UL 10C (1998)<br>UBC Standard 7-2 (1997)<br>UBC Standard 7-2 (1994) | 20 Minute-With & Without Hose Stream<br>Positive Pressure<br>Category C- Proprietary Frame |
| TEST REPORT   |  |

## **TEST REPORT**

Warnock Hersey Test Report No: WHI-495-0509 Intertek Test Report No(s): 3746699, 8772599, 3028781, 3035264, 3048460

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com