NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014306-R1

DATE: 01/14/2019

CERTIFICATION PROGRAM: Fire

COMPANY: Trimco Millwork

CODE: 868-1

REVISION DATE: <u>04/11/2023</u> EXPIRATION DATE: <u>01/31/2024</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION |
|--------------------------|---|
| Trimco Millwork | FyreWerks FC-20 |
| 1835 Commerce Avenue | 20 Minute Positive Pressure |
| Boise, ID 83715 | Side-Hinged Door |
| | Manufacturer Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations |
| | 1/2" Minimum Latch Throw Single & Double Swing Only |
| | Single Maximum Size: 4'0" x 8'0" Double Maximum Size: 7'0" x 8'0" Minimum Thickness: 1-3/4" |

| SPECIFICATION | PRODUCT RATING |
|--|---|
| UL 10(b) (2009) CAN/ULC-S104 (2015) UL 10(c) (2015) NFPA 252 (2012) | 20 Minute-Positive Pressure w/Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing) |

TEST REPORT

Intertek Test Report No: 3073306, 3084820, 3144298COQ-003, 3159384COQ-002, 3156802COQ-004, 3181657COQ-006, 3179089COQ-003, 10015449MID-001, 102627269MID-001, 103096847MID-001

Administrator's Signature: ___



NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Tel: (804) 684-5124 nami@namiinc.com