

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014314-R1
DATE: 01/14/2019
CERTIFICATION PROGRAM: Fire
COMPANY: Trimco Millwork
CODE: 868-1
REVISION DATE: 11/30/2022
EXPIRATION DATE: 01/31/2026

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Trimco Millwork 1835 Commerce Avenue Boise, ID 83715	Lynden 20 Minute L20SP Flush Particleboard Core Fire Door Assembly Manufacturer Specific Fire Doors for Single, Double Swing & Double Egress Installation in 20 Minute Locations 1/2" Minimum Latch Throw for Singles 3/4" Minimum Latch Throw for Double Single & Double Swing Only Single Maximum Size: 4'0" x 9'0" Double Maximum Size: 8'0" x 9'0" Double Egress Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
UL 10C (2001)(2009) UBC Standard 7-2 (1997)	20 Minute-Positive Pressure With Hose Stream Category A Door-No Additional Edge Seal Required (unless specified in individual manufacturer's listing) For Use in Welded or Knock-Down 16 & 18 Gauge Steel or Listed Category C Wood, Steel, Aluminum or Proprietary Frames (In accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3052139/3060684/3075954/3157236

Administrator's Signature: _____

A handwritten signature in black ink, appearing to be "S.H.O.", is written over the signature line.

**NATIONAL ACCREDITATION AND
MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124

nami@namiinc.com