## NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014320-R1

**DATE:** 01/17/2019

CERTIFICATION PROGRAM: <u>Fire</u>

COMPANY: <u>EL & EL Wood</u>

CODE: <u>2195-1</u>

REVISION DATE: <u>02/13/2023</u> EXPIRATION DATE: <u>01/31/2026</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Metrie EL & EL, LLC	Simpson Stile & Rail
13855 Ramona Avenue	Single Swing Wood Door
Chino, CA 91710	
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'6" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
UL 10b (2009) UL 10c (2009) (2015) (2016)	20 Minute-Positive Pressure With Hose Stream
CAN/ULC S104 (2010) (2015)	Category B Door-Additional Edge Seal
<b>UBC Standard 7-2 (1997)</b>	Required (unless specified in individual manufacturer's listing)  For Use in Category C Frame
	(or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

## **TEST REPORT**

Intertek Test Report No: 3089369COQ-005, 3137943COQ-003, 3157209COQ-005

She

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124/nami@namiinc.com