## **NOTICE OF PRODUCT CERTIFICATION**

ACCREDITED A	<b>CERTIFICATION NO:</b>	NI014322-R1
Sa round official Con	DATE:	01/17/2019
S N S N S N	<b>CERTIFICATION PROGRAM:</b>	Fire
	<b>COMPANY:</b>	EL & EL Wood
(MARCH AND	CODE:	<u>2195-1</u>
Con CEMENT INST	<b>REVISION DATE:</b>	02/13/2023
ATIFIED PRODUC	<b>EXPIRATION DATE:</b>	01/31/2026
And the second se		

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Metrie EL & EL, LLC	"Simpson Stile & Rail" Wood-Faced
13855 Ramona Avenue	Fire Door Assembly w/ Hose Stream
Chino, CA 91710	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations For use in any Category C - Standard or Proprietary Frame
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'6" x 8'0" Minimum Thickness: 1-3/4"

## **SPECIFICATION**

CAN/ULC S104 (2010) UL 10B (2009)(2015) UL 10C (2009)(2015)(2016) NFPA 252 (2012) **PRODUCT RATING** 

20 Minute-Positive Pressure With Hose Stream Category B - Additional Edge Sealing Required

## **TEST REPORT**

Intertek Test Report No: 3089369COQ-005; 3137943COQ-003; 3157209COQ-005; 102770454MID-001

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124 nami@namiinc.com