NOTICE OF PRODUCT CERTIFICATION

1065 ACCREDITED A	CERTIFICATION NO:	NI014323-R1
Sal Long Charles Con	DATE:	01/17/2019
S N N N N N N N N N N N N N N N N N N N	CERTIFICATION PROGRAM:	Fire
NAMI	COMPANY:	EL & EL Wood
(MARCH AND	CODE:	<u>2195-1</u>
Contraction of the second second	REVISION DATE:	02/13/2023
SATIFIED PRODUC	EXPIRATION DATE:	<u>01/31/2026</u>
and the second se		

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Metrie EL & EL, LLC	20 Minute Positive & Neutral Pressure
13855 Ramona Avenue	Flush or Molded Interior Side-Hinged
Chino, CA 91710	Door w/Particleboard Core
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"
	1

SPECIFICATION

NFPA 252 (1999) UL 10(b) (2009) ASTM E2074 (2000) CAN4-S104(ULC S104) UBC Standard 7-2 (1994/1997) UL 10(c) (1998) 20 Minute-Neutral/Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance

PRODUCT RATING

with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3137713COQ-007

Administrator's Signature:_

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124/nami@namiinc.com