NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014374-R1

DATE: 03/28/2019

CERTIFICATION PROGRAM: Fire

COMPANY: Orepac

CODE: <u>1234-1</u>

REVISION DATE: 08/01/2023

EXPIRATION DATE: 03/31/2023

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
Orepac Building Products, Inc. 30160 SW Orepac Avenue	Rogue Valley 20 Minute Positive Pressure MDF	
	Manufacturer Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations	
	1/2" Minimum Latch Throw Single & Double Swing Only	
	Single Maximum Size: 3'6" x 8'0" Double Maximum Size: 7'0" x 8'0" Minimum Thickness: 1-3/4"	

SPECIFICATION	PRODUCT RATING
UBC-7-2-97 UL 10C (1998)(2009) NFPA 252 (1999) CAN4 S104 (1985) CAN/ULC S104 (2010)	20 Minute-Positive Pressure w/Hose Stream Category A Door-No Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT	
Intertek Test Report No: 3049231/3049231a	

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com