NOTICE OF PRODUCT CERTIFICATION

STORS ACCREDITED AROUND	CERTIFICATION NO: DATE: CERTIFICATION PROGRAM:	<u>NI014474-R1 08/06/2019</u> Fire
	COMPANY:	Lumbermen's
CA GEMENT INSTIT	CODE:	<u>1021-1</u>
CATIFIED PRODUC	REVISION DATE:	06/22/2023
	EXPIRATION DATE:	<u>08/31/2026</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	
Lumbermen's Incorporated	Therma Tru 20 Minute Fiberglass Door
8715 Byron Commerce Drive Southwest	w/Proprietary Foam Core
Byron Center, MI 49315	(Simulated, Flush or Shaker Panel Type)
	Manufacture Specific Fire Door Frames for Single Swing Installation in 20 Minute Locations
	Single Door Maximum Size: 36" x 96" Shaker Single Door Maximum Size: 36" x 80"
	Minimum Thickness: 1-3/4"
	Minimum Thickness: 1-3/4"

SPECIFICATION

AA

UL 10C (2016) NFPA 252 (2012) 20 Minute-without Hose Stream Positive Pressure Category B- Additional Edge Sealing Required

PRODUCT RATING

TEST REPORT

Intertek Test Report No: 103875182MID-007

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124 Fax: (804) 684-5122