## **NOTICE OF PRODUCT CERTIFICATION**

ACCREDITED	<b>CERTIFICATION NO:</b>	NI014581-R1
S ONNI ACCREDITATO	DATE:	<u>12/12/2019</u>
MARKEN AND SOUTH	<b>CERTIFICATION PROGRAM:</b>	Fire
NAMI)	<b>COMPANY:</b>	TNT Door
( and a find the	CODE:	<u>2610-1</u>
Thagement INSTIT	<b>REVISION DATE:</b>	<u>10/30/2023</u>
ERTIFIED PRODUCT	<b>EXPIRATION DATE:</b>	<u>12/31/2025</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
TNT Door & Millwork, Inc.	20 Minute Positive & Neutral Pressure	
11400 West Executive Drive, Suite 8	Flush or Molded Interior Side-Hinged	
Boise, ID 83713	Door w/Particleboard Core	
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations	
	1/2" Minimum Latch Throw Single Swing Only	
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"	

## **SPECIFICATION**

NFPA 252 (1999) UL 10(b) (2009) ASTM E2074 (2000) CAN4-S104(ULC S104) UBC Standard 7-2 (1994/1997) UL 10(c) (1998)

## PRODUCT RATING

20 Minute-Neutral/Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

## **TEST REPORT**

Intertek Test Report No: 3137713COQ-007

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124 nami@namiinc.com