NOTICE OF PRODUCT CERTIFICATION

CERTIFICATION NO: N1014682-R1DATE: 02/12/2020	
CERTIFICATION PROGRAM: Fire	
COMPANY: Orepac	
CODE: 1234-1	
EXPIRATION DATE: 02/12/2026	
REVISION DATE: 04/11/2024	

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Orepac Building Products, Inc.	Frame Madeiras Especials Raised &
30160 SW Orepac Avenue	Flat Panel MDF Fire Door Assembly
Wilsonville, OR 97070	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"
	

SPECIFICATION

UL 10C (2016) NFPA 252 (2017)

PRODUCT RATING

20 Minute-Positive Pressure Without Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 103898617MID-005R1

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC-03/30/2023