## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI014925-R1

**DATE:** 08/07/2020

**CERTIFICATION PROGRAM:** Fire

**COMPANY:** Bjornstad Const.

**CODE:** <u>2644-1</u>

REVISION DATE: <u>08/31/2023</u> EXPIRATION DATE: <u>08/31/2024</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
<b>Bjornstad Construction Company</b>	20 Minute Neutral Pressure Fire Door	
1240 Texan Trail, Suite 102	Assemblies w/o Hose Stream	
Grapevine, TX 76051	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations	
	1/2" Minimum Latch Throw Single or Double Swing Only	
	Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"	

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999) UL 10B (2009) UBC Standard 7-2 (1997)	20 Minute-Neutral Pressure Without Hose Stream

## **TEST REPORT**

Intertek Test Report No: 3073067, 3043898, 307008-1, 100108677COQ-001, 3059877, J20012862-23, 3025659, 3192291COQ-005, 3048495, 3108034COQ-003, Warnock-Hershey Test Report No: WHI-495-1685, WHI-495-1197, WHI-495-0897

Administrator's Signature:	Shiel	
Transmission of Signature.		

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com