# **NOTICE OF PRODUCT CERTIFICATION**

ACCREDITE.	<b>CERTIFICATION NO:</b>	NI014933-R1
CATODO ANI. ACCREDITE PO	DATE:	08/31/2024
OS STATES	<b>CERTIFICATION PROGRAM:</b>	Fire
	<b>COMPANY:</b>	<b>Bjornstad Const.</b>
AND AND AND	CODE:	2644-1
CERCEMENT INSTI	<b>REVISION DATE:</b>	08/31/2023
ATFIED PRODUC	<b>EXPIRATION DATE:</b>	08/31/2024

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	<b>PRODUCT DESCRIPTION</b>
Bjornstad Construction Company	<b>Crest Doors Particleboard Core</b>
1240 Texan Trail, Suite 102	w/Fiberglass Cladding Fire Door
Grapevine, TX 76051	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Single Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

### SPECIFICATION

CAN4 S104 (1985)(2010) UL 10C (2001)(2009) NFPA 252 (2008)

#### PRODUCT RATING

20 Minute-Positive Pressure With Hose Stream Category B - Additional Edge Sealing System Required

#### **TEST REPORT**

Intertek Test Report No: 3160246MID-005

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124 nami@namiinc.com