NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO:
DATE:
CERTIFICATION PROGRAM:
COMPANY:
CODE:
EXPIRATION DATE:

NI013225	
05/31/2016	
Fire	
Millwork Sales	
434-1	
05/31/2020	

To verify that the "Notice of Product Certification" is valid, please visit <u>www.NAMICertification.com</u> to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Millwork Sales	Buffelen Woodworking 20 Minute Positive
1925 Parks Oaks Avenue	Pressure Stile & Rail Panel
Orlando, FL 32808	Side-Hinged Door
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Single Swing Maximum Size: 3'6" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION

PRODUCT RATING

NFPA 252 (2008) UL 10B (2001) UBC Standard 7-2 (1997) 20 Minute-Positive Pressure Without Hose Stream Category B - Additional Edge Sealing Required

TEST REPORT

Intertek Test Report No: 3148824MID-004b

Administrator's Signature:

ShO

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC. 4794 George Washington Memorial Highway

> Hayes, VA 23072 Tel: (804) 684-5124 Fax: (804) 684-5122