NOTICE OF PRODUCT CERTIFICATION

| CERTIFICATION NO: <u>NI011928-R4</u> DATE: <u>03/04/2014</u> CERTIFICATION PROGRAM: <u>Structural</u> COMPANY: <u>Origin</u> CODE: <u>1985-1</u> REVISION DATE: <u>10/22/2016</u> |
|--|
|--|

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

| COMPANY NAME AND ADDRESS | | PRODUCT DES | CRIPTION |
|------------------------------|--|------------------|-------------------|
| Origin USA, Inc. | Series "Easifold 3000" Glazed Aluminum | | |
| 771 Commerce Drive, Suite 16 | In-Swing Side-Hinged Doors | | |
| Venice, FL 34292 | w/ or w/o Track Riser | | |
| | Configuration: XX Glazing: IG-3/16" Tempered Glass/Laminate-3/16" Heat Strengthened Glass/0.090" DuPont SG Interlayer/3/16" Heat Strengthened Glass | | |
| | Frame: | W-1965mm(77.37") | H-2585mm(101.87") |
| | Leaf: | W-934mm(36.75") | H-2438mm(96") |
| | DLO: | W-762mm(30.00") | H-2286mm(90") |

| SPECIFICATION | PRODUCT RATING |
|---------------------------------|--|
| AAMA/WDMA/CSA 101/I.S.2/A440-08 | Class R-PG20 1965 x 2585 (77 x 102)-SHD Design Pressure: 957 Pa (20 psf) Positive Design Pressure: 2400 Pa (50 psf) Negative Design Pressure: 2640 Pa (55 psf) Water Penetration Resistance Test Pressure: 150 Pa (3.13 psf) Qualifies Configurations: X/XX |

Product Tested By: Report No: Expiration Date:

Architectural Testing Incorporated D0972.02-401-44

December 31, 2026

Administrator's Signature:

NATIONAL ACCREDITATION AND **MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 Fax: (804) 684-5122