NOTICE OF PRODUCT CERTIFICATION



CENTIFICATION NO.	<u> </u>
DATE:	0
CERTIFICATION PROGRAM:	ŀ
COMPANY:	Ī
CODE:	4
EXPIRATION DATE:	0

CEDTIEICATION NO.

NI013520
02/24/2017
Fire
Dyke Industries
452-1
02/28/2021

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Dyke Industries	Simpson Stile & Rail
10500 Northwest 95 th Avenue	Single Swing Wood Door
Medley, FL 33178	
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'6" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION

UL 10b (2009) UL 10c (2009) (2015) (2016) CAN/ULC S104 (2010) (2015) UBC Standard 7-2 (1997) PRODUCT RATING

20 Minute-Positive Pressure With Hose Stream Category B Door-Additional Edge Seal

Required (unless specified in individual manufacturer's listing)

For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3089369COQ-005, 3137943COQ-003, 3157209COQ-005

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC. 4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124/Fax: (804) 684-5122