

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI012008-R1
DATE: 06/09/2014
CERTIFICATION PROGRAM: Structural
COMPANY: Hope's
CODE: 656-1
REVISION DATE: 04/09/2018

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<p>Hope's Windows, Inc.</p> <p>84 Hopkins Avenue</p> <p>Jamestown, NY 14702</p>	<p>Series "SS30"</p> <p>Stainless Steel Direct Set</p> <p>Impact Rated Fixed Windows</p> <p>Configuration: O/O Glazing: Detention Glass by Century Glass- 1/4" Chemically Strengthened Glass/5mm Lexan Polycarbonate/5mm Lexan Polycarbonate /1/4" Chemically Strengthened Glass</p> <p>Overall: W-3004mm(118.25") H-2438mm(96")</p> <p>Individual: W-1524mm(60") H-2438mm(96")</p> <p>DLO: W-1371mm(54") H-2286mm(90")</p>

SPECIFICATION	PRODUCT RATING
<p>AAMA 450-10</p> <p>AAMA/WDMA/CSA 101/I.S.2/A440-11</p> <p>AAMA/WDMA/CSA 101/I.S.2/A440-08</p> <p>ASTM E1886-97/03/04/05/13/13a</p> <p>ASTM E1996-02/04/05/05b/06/09</p>	<p>Mulled Fenestration Rating: CW80</p> <p>Applied Rating: CW80</p> <p>Individual Rating:</p> <p>Class CW-PG80 1524 x 2438 (60 x 96)-FW</p> <p>Class CW-PG80 3004 x 2438 (118 x 96)-FW</p> <p>Design Pressure: 3840 Pa (80 psf)</p> <p>Wind Zone 4-Missile Level E</p> <p>Water Penetration Resistance Test Pressure: 580 Pa(12.11 psf) Canadian Air Infiltration/Exfiltration Rating: Fixed</p>

Product Tested By: Element Materials Technology
 Report No: ESP016682P-1556
 Expiration Date: May 31, 2028

Administrator's Signature: _____

**NATIONAL ACCREDITATION AND
 MANAGEMENT INSTITUTE, INC.**
 4794 George Washington Memorial Highway
 Hayes, VA 23072
 Tel: (804) 684-5124/Fax: (804) 684-5122