

# NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014299  
DATE: 01/08/2019  
CERTIFICATION PROGRAM: Fire  
COMPANY: Horizon Supply  
CODE: 2504-1  
EXPIRATION DATE: 01/31/2023

To verify that the "Notice of Product Certification" is valid, please visit [www.NAMICertification.com](http://www.NAMICertification.com) to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>Horizon Supply, LLC</b> <b>19998 Monte Way</b> <b>Caldwell, ID 83607</b>	<b>Lynden 20 Minute L20SP Flush</b> <b>Particleboard Core Fire Door Assembly</b>  Manufacturer Specific Fire Doors for Single, Double Swing & Double Egress Installation in 20 Minute Locations  1/2" Minimum Latch Throw for Singles 3/4" Minimum Latch Throw for Double Single & Double Swing Only  Single Maximum Size: 4'0" x 9'0" Double Maximum Size: 8'0" x 9'0" Double Egress Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
<b>UL 10C (2001)(2009)</b> <b>UBC Standard 7-2 (1997)</b>	<b>20 Minute-Positive Pressure</b> <b>With Hose Stream</b> <b>Category A Door-No Additional Edge Seal Required</b> (unless specified in individual manufacturer's listing) <b>For Use in Welded or Knock-Down 16 &amp; 18 Gauge Steel</b> <b>or Listed Category C Wood, Steel, Aluminum or</b> <b>Proprietary Frames</b> (In accordance with individual manufacturer's listing)

## TEST REPORT

Intertek Test Report No: 3052139/3060684/3075954/3157236

A handwritten signature in black ink, appearing to be 'S.M.', written over a horizontal line.

Administrator's Signature: \_\_\_\_\_

**NATIONAL ACCREDITATION AND  
MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124

Fax: (804) 684-5122

