

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014314
DATE: 01/14/2019
CERTIFICATION PROGRAM: Fire
COMPANY: Trimco Millwork
CODE: 868-1
EXPIRATION DATE: 01/31/2023

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Trimco Millwork 1835 Commerce Avenue Boise, ID 83715	Lynden 20 Minute L20SP Flush Particleboard Core Fire Door Assembly Manufacturer Specific Fire Doors for Single, Double Swing & Double Egress Installation in 20 Minute Locations 1/2" Minimum Latch Throw for Singles 3/4" Minimum Latch Throw for Double Single & Double Swing Only Single Maximum Size: 4'0" x 9'0" Double Maximum Size: 8'0" x 9'0" Double Egress Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
UL 10C (2001)(2009) UBC Standard 7-2 (1997)	20 Minute-Positive Pressure With Hose Stream Category A Door-No Additional Edge Seal Required (unless specified in individual manufacturer's listing) For Use in Welded or Knock-Down 16 & 18 Gauge Steel or Listed Category C Wood, Steel, Aluminum or Proprietary Frames (In accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3052139/3060684/3075954/3157236

A handwritten signature in black ink, appearing to be "S.M.", written over a horizontal line.

Administrator's Signature: _____

**NATIONAL ACCREDITATION AND
MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124

Fax: (804) 684-5122

