NOTICE OF PRODUCT CERTIFICATION

Company: Dyke Industries
9815 Brookford Road
Charlotte, NC 28241

Certification No.: NI012569.02-R1
Certification Date: 03/09/2015
Expiration Date: 03/31/2024
Revision Date: 11/21/2019

Product: Wood-Edge Steel Opaque Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites (w/Wood Frame unless noted)

Specification: TAS 201/202/203

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Opaque	3'0" x 8'0"	+70/-70	2.86 psf	Yes	NCTL-210-3121-1/CTLA919W Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
X Single	O/S	Opaque	3'0" x 8'0"	+70/-70	10.5 psf	Yes	NCTL-210-3121-1/CTLA919W Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
XX Double	I/S	Opaque	6'0" x 8'0"	+45/-50	2.86 psf	Yes	NCTL-210-3123-1 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
XX Double	O/S	Opaque	6'0" x 8'0"	+50/-45	6.75 psf	Yes	NCTL-210-3123-1 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
XO/OX Single w/Sidelite	I/S	Opaque Door Glazed Sidelite	6'0" x 8'0"	+45/-50	2.86 psf	Door-Yes Sidelite-No	NCTL-210-3123-1 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
XO/OX Single w/Sidelites	O/S	Opaque Door Glazed Sidelite	6'0" x 8'0"	+50/-45	6.75 psf	Door-Yes Sidelite-No	NCTL-210-3123-1 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
OXO Single w/Sidelites	I/S	Opaque Door Glazed Sidelites	9'0" x 8'0"	+45/-50	2.86 psf	Door-Yes Sidelites-No	NCTL-210-3123-1 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
OXO Single w/Sidelites	O/S	Opaque Door Glazed Sidelites	9'0" x 8'0"	+50/-45	6.75 psf	Door-Yes Sidelites-No	NCTL-210-3123-1 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
OXXO Double w/Sidelites	I/S	Opaque Doors Glazed Sidelites	12'4" x 8'0"	+45/-50	2.86 psf	Doors-Yes Sidelites-No	NCTL-210-3123-1 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Detail-MA-FL0129-05
OXXO Double w/Sidelites	O/S	Opaque Doors Glazed Sidelites	12'4" x 8'0"	+50/-45	6.75 psf	Doors-Yes Sidelites-No	NCTL-210-3123-1 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Detail-MA-FL0129-05

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____