## **NOTICE OF PRODUCT CERTIFICATION**



<b>CERTIFICATION NO:</b>	<u>N1014</u>
DATE:	<u>12/12/</u>
<b>CERTIFICATION PROGRAM:</b>	Fire
<b>COMPANY:</b>	TNT
CODE:	<b>2610-</b> 1
<b>EXPIRATION DATE:</b>	12/31/

NI014580	
12/12/2019	
Fire	
TNT Door	
2610-1	
12/31/2023	

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
TNT Door & Millwork, Inc.	Lynden 20 Minute L20SP Flush	
11400 West Executive Drive, Suite 8	Particleboard Core Fire Door Assembly	
Boise, ID 83713	Manufacturer Specific Fire Doors for Single, Double Swing & Double Egress Installation in 20 Minute Locations	
	<ul><li>1/2" Minimum Latch Throw for Singles</li><li>3/4" Minimum Latch Throw for Double Single &amp; Double Swing Only</li></ul>	
	Single Maximum Size: 4'0" x 9'0" Double Maximum Size: 8'0" x 9'0" Double Egress Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"	

## **SPECIFICATION**

UL 10C (2001)(2009) UBC Standard 7-2 (1997) PRODUCT RATING

20 Minute-Positive Pressure With Hose Stream Category A Door-No Additional Edge Seal Required (unless specified in individual manufacturer's listing) For Use in Welded or Knock-Down 16 & 18 Gauge Steel or Listed Category C Wood, Steel, Aluminum or

**Proprietary Frames** (In accordance with individual manufacturer's listing)

## **TEST REPORT**

Intertek Test Report No: 3052139/3060684/3075954/3157236

Sh.

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5122