
## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO: NI014938** 

**DATE:** 08/20/2020

**CERTIFICATION PROGRAM:** 

**COMPANY:** BMC Millwork

Fire

CODE: <u>1665-1</u>

**EXPIRATION DATE: 08/31/2024** 

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
BMC Millwork Corporation 399 Northpoint Parkway	Steve's & Sons/Crest Doors Particleboard Core/Wood Veneer	
	Manufacturer Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations	
	1/2" Minimum Latch Throw Single & Double Swing Only	
	Single Maximum Size: 4'0" x 9'0" Double Maximum Size: 8'0" x 9'0" Minimum Thickness: 1-3/4"	

SPECIFICATION	PRODUCT RATING
UBC-7-2-97 UL 10C (1998)(2009) NFPA 252 (1995)(2008)	20 Minute-Positive Pressure w/o Hose Stream Category A Door-No Additional Edge Seal Required Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT	
Warnock Hershey Test Report No: WHI-495-1367	

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5122