## **NOTICE OF PRODUCT CERTIFICATION**



<b>CERTIFICATION NO:</b>
DATE:
<b>CERTIFICATION PROGRAM:</b>
COMPANY:
CODE:
<b>EXPIRATION DATE:</b>

NI015032	
10/29/2020	
Fire	
North State	
2702-1	
10/31/2024	

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
North State Millwork Corporation	Jeld Wen 45-60 Minute
2708 West Raleigh Boulevard	<b>Profiled Core Side-Hinged Door</b>
Rocky Mount, NC 27803	w/Universal or Universal HD Core
	Manufacturer Specific Fire Doors for Single & Double Swing Installation in 45-60 Minute Locations
	1/2" Minimum Latch Throw
	Single & Double Swing Only
	(Double Egress Not Allowed)
	Single Maximum Size: 3'6" x 7'0"
	Single Maximum Size: 3'0" x 8'0"
	Double Maximum Size: 7'0" x 7'0"
	Minimum Thickness: 1-3/4"

## **SPECIFICATION**

UL 10(c) (2009/2016) CAN/ULC-S104 (2015) NFPA 252 (2012) PRODUCT RATING

45-60 Minute-Positive Pressure w/Hose Stream Category A Door-No Additional Edge Seal Required For Use in 16 & 18 Gauge Steel Frames (or may also be installed in Category C or Category C-Proprietary in accordance with individual manufacturer's listing)

## **TEST REPORT**

Intertek Test Report No: G103003006MID-008, WHI-495-1314

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 Fax: (804) 684-5122