

NOTICE OF PRODUCT CERTIFICATION



Company: Simpson Door Company
400 Simpson Avenue
McCleary, WA 98557

Certification No.: NI010390-R3 Pg 1 of 4
Certification Date: 10/19/2010
Expiration Date: 06/30/2031
Revision Date: 04/10/2024

Product: Series “Dowel” and Series “Mortise and Tenon” Wood French Door/
Series “Dowel” and Series “Mortise and Tenon” Wood Fixed Panel
Specifications Tested To: ASTM E283-04/ASTM E547-00/ASTM E330-02

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S or O/S	Glazed	3'1" x 8'2"	+35/-35	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/Max DLO: 2'3" x 6'10" Glazing: IG-1/8" Tempered Glass
X Single	I/S or O/S	Glazed	3'1" x 8'2"	+50/-50	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/Max DLO: 2'3" x 6'10" Glazing: IG-1/8" Tempered Glass/w/Surface Bolts
X Single	I/S or O/S	Opaque	3'1" x 8'2"	+35/-35	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"
X Single	I/S or O/S	Opaque	3'1" x 8'2"	+50/-50	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/w/Surface Bolts
XX Double	I/S or O/S	Glazed	6'2" x 8'2"	+35/-35	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/Max DLO: 2'3" x 6'10" Glazing: IG-1/8" Tempered Glass
XX Double	I/S or O/S	Glazed	6'2" x 8'2"	+50/-50	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/Max DLO: 2'3" x 6'10" Glazing: IG-1/8" Tempered Glass/w/Surface Bolts
XX Double	I/S or O/S	Opaque	6'2" x 8'2"	+35/-35	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"
XX Double	I/S or O/S	Opaque	6'2" x 8'2"	+50/-50	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/w/Surface Bolts

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/Email: nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____

NOTICE OF PRODUCT CERTIFICATION



Company: Simpson Door Company
400 Simpson Avenue
McCleary, WA 98557

Certification No.: NI010390-R3 Pg 2 of 4
Certification Date: 10/19/2010
Expiration Date: 06/30/2031
Revision Date: 04/10/2024

Product: Series “Dowel” and Series “Mortise and Tenon” Wood French Door/
Series “Dowel” and Series “Mortise and Tenon” Wood Fixed Panel
Specifications Tested To: ASTM E283-04/ASTM E547-00/ASTM E330-02

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S or O/S	Glazed	3'1" x 8'2"	+35/-35	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/18 Lite Glazing: IG-1/8" Tempered Glass
X Single	I/S or O/S	Glazed	3'1" x 8'2"	+50/-50	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/18 Lite Glazing: IG-1/8" Tempered Glass/w/Surface Bolts
X Single	I/S or O/S	Glazed	3'1" x 8'2"	+35/-35	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/9 Lite Glazing: Monolithic- 1/8" Tempered Glass
X Single	I/S or O/S	Glazed	3'1" x 8'2"	+50/-50	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/9 Lite Glazing: Monolithic- 1/8" Tempered Glass/w/Surface Bolts
XX Double	I/S or O/S	Glazed	6'2" x 8'2"	+35/-35	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/18 Lite Glazing: IG-1/8" Tempered Glass
XX Double	I/S or O/S	Glazed	6'2" x 8'2"	+50/-50	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/18 Lite Glazing: IG-1/8" Tempered Glass/w/Surface Bolts
XX Double	I/S or O/S	Glazed	6'2" x 8'2"	+35/-35	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/9 Lite Glazing: IG-1/8" Tempered Glass
XX Double	I/S or O/S	Glazed	6'2" x 8'2"	+50/-50	No	CCLI-10-115/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'11"/9 Lite Glazing: IG-1/8" Tempered Glass/w/Surface Bolts

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Email: nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____

A handwritten signature in black ink, appearing to be 'S.M.', is written over a horizontal line that serves as the signature line.

NOTICE OF PRODUCT CERTIFICATION



Company: Simpson Door Company
400 Simpson Avenue
McCleary, WA 98557

Certification No.: NI010390-R3 Pg 3 of 4
Certification Date: 10/19/2010
Expiration Date: 06/30/2031
Revision Date: 04/10/2024

Product: Series “Dowel” and Series “Mortise and Tenon” Wood French Door/
Series “Dowel” and Series “Mortise and Tenon” Wood Fixed Panel
Specifications Tested To: ASTM E283-04/ASTM E547-00/ASTM E330-02

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S or O/S	Glazed	3’1” x 8’2”	+35/-35	No	CCLI-10-115/W-1464-Mortise & Tenon Max Panel Size: 3’0” x 7’11” Glazing: IG-1/8” Tempered Glass
X Single	I/S or O/S	Glazed	3’1” x 8’2”	+50/-50	No	CCLI-10-115/W-1464-Mortise & Tenon Max Panel Size: 3’0” x 7’11” Glazing: IG-1/8” Tempered Glass/w/Surface Bolts
X Single	I/S or O/S	Opaque	3’1” x 8’2”	+35/-35	No	CCLI-10-115/W-1464-Mortise & Tenon Max Panel Size: 3’0” x 7’11”
X Single	I/S or O/S	Opaque	3’1” x 8’2”	+50/-50	No	CCLI-10-115/W-1464-Mortise & Tenon Max Panel Size: 3’0” x 7’11”/w/Surface Bolts
XX Double	I/S or O/S	Glazed	6’2” x 8’2”	+35/-35	No	CCLI-10-115/W-1464-Mortise & Tenon Max Panel Size: 3’0” x 7’11” Glazing: IG-1/8” Tempered Glass
XX Double	I/S or O/S	Glazed	6’2” x 8’2”	+50/-50	No	CCLI-10-115/W-1464-Mortise & Tenon Max Panel Size: 3’0” x 7’11” Glazing: IG-1/8” Tempered Glass/w/Surface Bolts
XX Double	I/S or O/S	Opaque	6’2” x 8’2”	+35/-35	No	CCLI-10-115/W-1464-Mortise & Tenon Max Panel Size: 3’0” x 7’11”
XX Double	I/S or O/S	Opaque	6’2” x 8’2”	+50/-50	No	CCLI-10-115/W-1464-Mortise & Tenon Max Panel Size: 3’0” x 7’11”/w/Surface Bolts

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/Email: nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____

A handwritten signature in black ink, appearing to be 'S.D.', written over a horizontal line.

NOTICE OF PRODUCT CERTIFICATION



Company: Simpson Door Company
400 Simpson Avenue
McCleary, WA 98557

Certification No.: NI010390-R3 Pg 4 of 4
Certification Date: 10/19/2010
Expiration Date: 06/30/2031
Revision Date: 04/10/2024

Product: Series “Dowel” and Series “Mortise and Tenon” Wood French Door/
Series “Dowel” and Series “Mortise and Tenon” Wood Fixed Panel
Specifications Tested To: ASTM E283-04/ASTM E547-00/ASTM E330-02

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S or O/S	Glazed	3'1" x 8'2"	+40/-40	No	CCLI-10-115/W-1464-Mortise & Tenon/Multi-Point Hardware Max Panel Size: 3'0" x 7'11" Glazing: IG-1/8" Tempered Glass
X Single	I/S or O/S	Opaque	3'1" x 8'2"	+40/-40	No	CCLI-10-115/W-1464-Mortise & Tenon/Multi-Point Hardware Max Panel Size: 3'0" x 7'11"
XX Double	I/S or O/S	Opaque	6'2" x 8'2"	+40/-40	No	CCLI-10-115/W-1464-Mortise & Tenon/Multi-Point Hardware Max Panel Size: 3'0" x 7'11" Glazing: IG-1/8" Tempered Glass
XX Double	I/S or O/S	Opaque	6'2" x 8'2"	+40/-40	No	CCLI-10-115/W-1464-Mortise & Tenon/Multi-Point Hardware Max Panel Size: 3'0" x 7'11"
O Single	Fixed	Glazed	3'1" x 8'2"	+50/-50	No	CCLI-10-115/Wood Fixed Door/Transom Max Panel Size: 3'0" x 7'11" Glazing: IG-1/8" Tempered Glass
O Single	Fixed	Glazed	3'1" x 8'2"	+50/-50	No	CCLI-10-115/Wood Fixed Door-Dowel Construction Max Panel Size: 3'0" x 7'11" Glazing: Monolithic-1/8" Tempered Glass
O Single	Fixed	Glazed	3'1" x 8'2"	+50/-50	No	CCLI-10-115/Wood Fixed Door-Dowel Construction Max Panel Size: 3'0" x 7'11" / 18 Lite Glazing: Monolithic-1/8" Tempered Glass
O Single	Fixed	Glazed	3'1" x 8'2"	+50/-50	No	CCLI-10-115/Wood Fixed Door-Dowel Construction Max Panel Size: 3'0" x 7'11" / 9 Lite Glazing: Monolithic-1/8" Tempered Glass

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Email: nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____