

# NOTICE OF PRODUCT CERTIFICATION



**Company:** Simpson Door Company  
400 Simpson Avenue  
McCleary, WA 98557

**Certification No.:** NI010406-R4 Pg 1 of 2  
**Certification Date:** 11/16/2010  
**Expiration Date:** 06/30/2031  
**Revision Date:** 04/10/2024

**Product:** Series “Dowel” and Series “Mortise and Tenon” Wood French Door  
**Specifications Tested To:** ASTM E283-04/ASTM E547-00/ASTM E330-02

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S or O/S	Glazed	3’2” x 7’3”	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3’0” x 7’0” Monolithic Glazing: 1/8” Tempered Glass
X Single	I/S or O/S	Glazed	3’2” x 7’3”	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3’0” x 7’0”/9-Lite Monolithic Glazing: 1/8” Tempered Glass
X Single	I/S or O/S	Glazed	3’2” x 7’3”	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3’0” x 7’0”/15-Lite Monolithic Glazing: 1/8” Tempered Glass
X Single	I/S or O/S	Opaque	3’2” x 7’3”	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3’0” x 7’0”
OX/XO Single w/Sidelite	I/S or O/S	Door-Opaque Sidelite-Glazed	4’11” x 7’3”	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3’0” x 7’0”/Sidelite-5 Lite Monolithic Glazing: 1/8” Tempered Glass
O XO Single w/Sidelites	I/S or O/S	Door-Opaque Sidelite-Glazed	6’5” x 7’3”	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3’0” x 7’0”/Sidelite-5 Lite Monolithic Glazing: 1/8” Tempered Glass
X Single	I/S or O/S	Glazed	3’2” x 7’3”	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3’0” x 7’0” Door Glazing: IG-1/8” Tempered Glass
OX/XO Single w/Sidelites	I/S or O/S	Door-Glazed Sidelites-Glazed	4’11” x 7’3”	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3’0” x 7’0” Door Glazing: IG-1/8” Tempered Glass Sidelite Monolithic Glazing-1/8” Tempered Glass

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072  
Tel: (804) 684-5124/Email: [nami@namiinc.com](mailto:nami@namiinc.com)

NAMI AUTHORIZED SIGNATURE: \_\_\_\_\_

# NOTICE OF PRODUCT CERTIFICATION



**Company:** Simpson Door Company  
400 Simpson Avenue  
McCleary, WA 98557

**Certification No.:** NI010406-R4 Pg 2 of 2  
**Certification Date:** 11/16/2010  
**Expiration Date:** 06/30/2031  
**Revision Date:** 04/10/2024

**Product:** Series “Dowel” and Series “Mortise and Tenon” Wood French Door  
**Specifications Tested To:** ASTM E283-04/ASTM E547-00/ASTM E330-02

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Missile Impact Rated	Test Report Number Drawing Number & Comments
OXO Single w/Sidelites	I/S or O/S	Door-Glazed Sidelites-Glazed	6'5" x 7'3"	+50/-50	No	CCLI-10-162/W-1464-Dowel Construction Max Panel Size: 3'0" x 7'0" Door Glazing: IG-1/8" Tempered Glass Sidelite Monolithic Glazing- 1/8" Tempered Glass
X Single	I/S or O/S	Opaque	3'2" x 7'3"	+50/-50	No	CCLI-10-162/W-1464-Mortise & Tenon Construction Multi-Point Hardware Max Panel Size: 3'0" x 7'0"
X Single	I/S or O/S	Glazed	3'2" x 7'3"	+50/-50	No	CCLI-10-162/W-1464-Mortise & Tenon Construction Multi-Point Hardware Max Panel Size: 3'0" x 7'0"/Full Lite Glazing: IG-1/8" Tempered Glass
X Single	I/S or O/S	Glazed	3'2" x 7'3"	+50/-50	No	CCLI-10-162/W-1464-Mortise & Tenon Construction Max Panel Size: 3'0" x 7'0"/Half Lite Glazing: IG-1/8" Tempered Glass

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072  
Tel: (804) 684-5124/Email: [nami@namiinc.com](mailto:nami@namiinc.com)

NAMI AUTHORIZED SIGNATURE: \_\_\_\_\_