



NOTICE OF PRODUCT CERTIFICATION

Company: JELD-WEN Doors
 3737 Lakeport Drive
 Klamath Falls, OR 97601

Certification No.: NI011065-R8
Certification Date: 04/18/2012
Expiration Date: 04/30/2028
Revision Date: 08/08/2022

Product: 25 Ga. Steel Wood Edge Glazed & Opaque Doors w/Glazed Sidelites (w/wood frame)

Specification: ASTM E283-04/E330-02/E331-00/AAMA 1304-02

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Test Report Number Drawing Number & Comments
OXXO Double w/Sidelites	I/S	Door-Glazed Sidelite-Glazed	12'5" x 6'10"	+35/-35 psf	NCTL 210-3804-1/NCTL 210-3801-1/FL 1939/W-1517/W-1897/W-1905/W-2003/W-2025/W-2039 Max Panel Size: 3'0" x 6'8"/Daylight Opening: 1'9" x 5'3" Glazing: IG- 1/8" Tempered w/AFCO A-276 Sill Installation Details: JW132012FL
OXXO Double w/Sidelites	I/S	Door-Glazed Sidelite-Glazed	12'5" x 6'10"	+35/-35 psf	NCTL 210-3804-1/SJW2010-146/FL 1939W-1517/W-1897/W-1905/W-2003/W-2025/W-2039 Max Panel Size: 3'0" x 6'8"/Daylight Opening: 1'9" x 5'3" Glazing: IG- 1/8" Tempered w/Endura LZA1L5625DSR Sill Installation Details: JW132012FL
OXXO Double w/Sidelites	O/S	Door-Glazed Sidelite-Glazed	12'5" x 6'9"	+35/-35 psf	NCTL 210-3804-2/NCTL 210-3801-1/FL 1939/W-1517/W-1897/W-1905/W-2003/W-2025/W-2039 Max Panel Size: 3'0" x 6'8"/Daylight Opening: 1'9" x 5'3" Glazing: IG- 1/8" Tempered w/AFCO A-117 Sill Installation Details: JW132012FL
OXXO Double w/Sidelites	I/S	Door-Opaque Sidelite-Glazed	12'5" x 6'10"	+35/-35 psf	NCTL 210-3804-1/NCTL 210-3801-1/FL 1937/W-1517/W-1897/W-1905/W-2003/W-2025/W-2039 Max Panel Size: 3'0" x 6'8"/Daylight Opening: 1'9" x 5'3" Glazing: IG- 1/8" Tempered w/AFCO A-276 Sill Installation Details: JW122012FL
OXXO Double w/Sidelites	I/S	Door-Opaque Sidelite-Glazed	12'5" x 6'10"	+35/-35 psf	NCTL 210-3804-1/SJW2010-146/FL 1937/w-1517/W-1897/W-1905/W-2003/W-2025/W-2039 Max Panel Size: 3'0" x 6'8"/Daylight Opening: 1'9" x 5'3" Glazing: IG- 1/8" Tempered w/Endura LZA1L5625DSR Sill Installation Details: JW122012FL
OXXO Double w/Sidelites	O/S	Door-Opaque Sidelite-Glazed	12'5" x 6'9"	+35/-35 psf	NCTL 210-3804-2/NCTL 210-3801-1/FL 1937/W-1517/W-1897/W-1905/W-2003/W-2025/W-2039 Max Panel Size: 3'0" x 6'8"/Daylight Opening: 1'9" x 5'3" Glazing: IG- 1/8" Tempered w/AFCO A-117 Sill Installation Details: JW122012FL

**National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
 Tel: (804) 684-5124/nami@namiinc.com**

NAMI AUTHORIZED SIGNATURE: _____