

NOTICE OF PRODUCT CERTIFICATION



Company: Wincore Window Company, LLC
 250 Staunton Turnpike
 Parkersburg, WV 26104

Certification No.: NI011132.02-R5
Certification Date: 06/05/2012
Expiration Date: 06/30/2028
Revision Date: 05/22/2023

Product: Wincore “Impact” Fiberglass Glazed Entry Door w/ or w/o Impact Rated Sidelites

Specification: TAS 201-94/202-94/203-94/ASTM E330-02/E331-00/E283-04/E1886-05/E1996-06

Impact Glazing (where applicable): Laminate-1/8” Annealed Glass/0.090” Interlayer Saflex by Solutia/1/8” Annealed Glass/1/8” Tempered Glass

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S or O/S	Glazed	3’2” x 6’10”	+65/-65	I/S 0.0 psf O/S 11.25 psf	Yes	TEL 01390365.0/TEL 01390365-WIN Maximum Panel Size: 3’0” x 6’8”/DLO: 5’3” x 1’9” Wood or PF Composite Jamb Installation Details: FL-15631.4(1-8) Florida Product Approval: FL#15631.4
OX/XO Single w/Sidelite	I/S or O/S	Door-Glazed Sidelite-Glazed	6’5” x 6’10”	+65/-65	I/S 0.0 psf O/S 11.25 psf	Door-Yes Sidelite-Yes	TEL 01390365.0/TEL 01390365-WIN Maximum Panel Size: 3’0” x 6’8”/DLO: 5’3” x 1’9” Wood or PF Composite Jamb Installation Details: FL-15631.5(1-12) Florida Product Approval: FL#15631.5
OXO Single w/Sidelites	I/S or O/S	Door-Glazed Sidelites-Glazed	9’8” x 6’10”	+65/-65	I/S 0.0 psf O/S 11.25 psf	Door-Yes Sidelite-Yes	TEL 01390365.0/TEL 01390365-WIN Maximum Panel Size: 3’0” x 6’8”/DLO: 5’3” x 1’9” Wood or PF Composite Jamb Installation Details: FL-15631.5(1-12) Florida Product Approval: FL#15631.5
OXXO Double w/Sidelites	I/S or O/S	Door-Glazed Sidelites-Glazed	12’8” x 6’10”	+50/-50	I/S 0.0 psf O/S 9.0 psf	Door-Yes Sidelite-Yes	TEL 01390365.0/TEL 01390365-WIN Maximum Panel Size: 3’0” x 6’8”/DLO: 5’3” x 1’9” Wood or PF Composite Jamb Installation Details: FL-15631.6(1-12) Florida Product Approval: FL#15631.6

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5124

NAMI AUTHORIZED SIGNATURE: _____