## NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI011980.10-R4

**DATE:** 05/20/2014

**CERTIFICATION PROGRAM:** <u>Structural</u>

**COMPANY:** Can-Save

CODE: <u>1347-1</u> REVISION DATE: <u>03/17/2021</u>

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Can-Save Building Materials	"Doorsmith Entrance"
411 Bayview Drive	In-Swing Glazed Steel w/Wood Edge
Barrie, ON L4M 6P4	Side-Hinged Door
	w/Insert Glazing & Adjustable Cap
	Configuration: OXO Glazing: Insulated Glass (Tempered)
	Frame: W-2489mm(112.18") H-2481mm(97.68")
	Panel: W-908mm(35.75") H-2413mm(95.00")
	DLO: W-584mm(23.00") H-2057mm(81.00")

SPECIFICATION	PRODUCT RATING
AAMA/WDMA/CSA 101/I.S.2/A440-08 CSA A440S1-09	Class R-PG35 2850 x 2481 (112 x 98)-SHD Positive Design Pressure: 1680 Pa (35 psf)
	Negative Design Pressure: 1920 Pa (40 psf) Water Penetration Resistance Test Pressure: 260 Pa (5.25 psf)
	Canadian Air Infiltration/Exfiltration Level: A3  Qualifies Configurations: O/X/OX/XO/OXO

Product Tested By: National Certified Testing Laboratories

Report No: NCTL-110-17014-7/W-1680/W-1681/W-1726

Expiration Date: **January 31, 2026** 

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Haves, VA 23072

Tel: (804) 684-5124 Fax: (804) 684-5122