

# NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI012099.04-R3  
DATE: 08/21/2014  
CERTIFICATION PROGRAM: Structural  
COMPANY: Wincore  
CODE: 1640-1  
REVISION DATE: 10/18/2022

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>Wincore Window Company, LLC</b> <b>250 Staunton Turnpike</b> <b>Parkersburg, WV 26104</b>	<b>Series "400/500"</b> <b>Vinyl Sliding Patio Door</b>  Configuration: XOO Glazing: Insulating Glass (Tempered) or IG-1/8" Tempered Glass/Laminate-1/8" Annealed Glass/0.030" PVB Interlayer/1/8" Annealed Glass  Frame: W-2650mm(104.33") H-2440mm(96.06") Panel: W-900mm(35.43") H-2335mm(91.93") DLO: W-738mm(29.06") H-2174mm(85.59")

SPECIFICATION	PRODUCT RATING
<b>AAMA/WDMA/CSA 101/I.S.2/A440-17</b> <b>AAMA/WDMA/CSA 101/I.S.2/A440-11</b> <b>AAMA/WDMA/CSA 101/I.S.2/A440-08</b>	<b>Class R-PG35 2650 x 2440 (104 x 96)-SD</b> <b>Design Pressure: 1680 Pa (35 psf)</b> <b>Negative Design Pressure: 1680 Pa (35 psf)</b> <b>Water Penetration Resistance Test Pressure: 400Pa(8.25 psf)</b> <b>Canadian Air Infiltration/Exfiltration Level: A3</b>

Product Tested By: Air-Ins, Inc.  
Report No: AI-04257-H2/W-1713/W-1920/W-2050  
Expiration Date: July 31, 2026

Administrator's Signature: \_\_\_\_\_

**NATIONAL ACCREDITATION AND  
MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124

[nami@namiinc.com](mailto:nami@namiinc.com)