NOTICE OF PRODUCT CERTIFICATION

Company: **Dyke Industries**
9815 Brookford Street
Charlotte, NC 28241

Certification No.: **NI012570.05-R2**
Certification Date: **03/09/2015**
Expiration Date: **03/31/2029**
Revision Date: **11/12/2024**

Product: **Fiberglass Impact Glazed Inswing or Outswing Door w/ and w/o Impact Rated Sidelites (w/Wood Frame unless noted)**
Specification: **TAS 202/ASTM E330/ASTM E1886/ASTM E1996**
Impact Rating: Wind Zone 4-Missile Level D

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 6'8"	+52/-52	2.86 psf	Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
X Single	O/S	Glazed	3'0" x 6'8"	+55/-55	6.00 psf 8.25 psf*	Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
XX Double	I/S	Glazed	6'0" x 6'8"	+52/-52	2.86 psf	Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
XX Double	O/S	Glazed	6'0" x 6'8"	+55/-55	6.00 psf 8.25 psf*	Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
XO/OX Single w/Sidelite	I/S	Glazed Door Glazed Sidelite	6'0" x 6'8"	+52/-52	2.86 psf	Door-Yes Sidelite-Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
XO/OX Single w/Sidelites	O/S	Glazed Door Glazed Sidelite	6'0" x 6'8"	+55/-55	6.00 psf 8.25 psf*	Door-Yes Sidelite-Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
OXO Single w/Sidelites	I/S	Glazed Door Glazed Sidelites	9'0" x 6'8"	+52/-52	2.86 psf	Door-Yes Sidelites-Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
OXO Single w/Sidelites	O/S	Glazed Door Glazed Sidelites	9'0" x 6'8"	+55/-55	6.00 psf 8.25 psf*	Door-Yes Sidelites-Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
OXXO Double w/Sidelites	I/S	Glazed Doors Glazed Sidelites	12'6" x 6'8"	+52/-52	2.86 psf	Doors-Yes Sidelites-Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07
OXXO Double w/Sidelites	O/S	Glazed Doors Glazed Sidelites	12'6" x 6'8"	+55/-55	6.00 psf 8.25 psf*	Doors-Yes Sidelites-Yes	NCTL-210-3389-1 Maximum Panel Size: 3'0" x 6'8" Anchor Detail-MA-FL0162-07

***Denotes High Dam Threshold Design**

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/Email: nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____