NOTICE OF PRODUCT CERTIFICATION

| 1065 ACCREDITED A | | |
|----------------------|-------------------------------|--------------------|
| W JONNL ACCREDITADOG | CERTIFICATION NO: | <u>NI012743-R3</u> |
| Nog Nin An Internet | DATE: | 07/22/2015 |
| (NAMI) | CERTIFICATION PROGRAM: | Structural |
| In the second | COMPANY: | <u>Kennedy</u> |
| C. AGEMENT INSTIT | CODE: | <u>1978-1</u> |
| EATIFIED PRODUC | REVISION DATE: | <u>10/16/2023</u> |
| | | |

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | | PRODUCT DESCRIPTION | | |
|------------------------------|--|---------------------|---------------|--|
| Natural Light Energy Systems | | Series "H.C. | M.A'' | |
| dba Kennedy Skylights | Curb-Mounted Aluminum Skylight | | | |
| 5294 Tower Way | | | | |
| Sanford, FL 32773 | Configuration: O Outer Dome: 0.093" thick Polycarbonate Inner Dome: 0.040" thick Polycarbonate | | | |
| | Frame: | W-1524mm(60") | H-1524mm(60") | |
| | Sash: | W-1321mm(52") | H-1321mm(52") | |
| | DLO: | W-1245mm(49") | H-1245mm(49") | |

| SPECIFICATION | PRODUCT RATING |
|--------------------|--|
| TAS 201/202/203-94 | Design Pressure: ±3830 Pa (80 psf) Large Missile Impact Rated |

Product Tested By: Report No: Expiration Date: National Certified Testing Laboratories NCTL-210-3992-01 December 31, 2024

Administrator's Signature:

AA

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC. 4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Email: <u>nami@namiinc.com</u>