NOTICE OF PRODUCT CERTIFICATION

| CERTIFICATION PROCESSION | CERTIFICATION NO: DATE: CERTIFICATION PROGRAM: COMPANY: CODE: REVISION DATE: | <u>NI012879.03-R2</u> 01/23/2018 <u>Structural</u> YKK 1772-1 06/20/2022 | |
|--------------------------|---|---|--|
| CERTIFIED PRODUCT | CERTIFICATION PROGRAM: COMPANY: CODE: | 01/23/2018 Structural YKK 1772-1 | |

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | | PRODUCT DESCRIPTION | | | | |
|---|------|---|------------------|-----------------|--|--|
| YKK AP America, Inc. | | Series "YES SSG TUH" | | | | |
| 270 Riverside Pkwy, Suite 100 | | Aluminum Project-Out Awning Window | | | | |
| Austell, GA 30168 | | w/4-Point Multi-Lock | | | | |
| | | Configuration: X Glazing: IG-1/4" Tempered Glass/Laminate-5/32" Heat Strengthened Glass/0.060" DuPont PVB Interlayer/5/32 Heat" Strengthened Glass | | | | |
| | | Frame: | W-1524mm(60") | H-914mm(36") | | |
| | | Vent: | W-1511mm(59.5") | H-902mm(35.5") | | |
| | | DLO: | W-1429mm(56.25") | H-819mm(32.25") | | |
| SPECIFICATION | | PRODUCT RATING | | | | |
| ASTM E1886-05/E1996-05 TAS 201/202/203-94 | | Design Pressure: ±3830 Pa (80 psf) Wind Zone 4 - Missile Level A Small Missile Impact Rated | | | | |
| Product Tested By:Architectural Testing IncorporatedReport No:D5961.01-550-18/D5961.05-550-18/D5961.06-550-18/D5961.08-550-18Expiration Date:April 30, 2026 | | | | | | |
| Administrator's Signat | ure: | ni | | | | |

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC. 4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124

Email: <u>nami@namiinc.com</u>