NOTICE OF PRODUCT CERTIFICATION

| ERTIFICATION NO: <u>NI012930.06-R3</u> DATE: <u>06/22/2016</u> CATION PROGRAM: <u>Structural</u> COMPANY: <u>Great Lakes</u> CODE: <u>1411-1</u> REVISION DATE: <u>02/14/2022</u> |
|--|
| |

To verify that the "Notice of Product Certification" is valid, please visit <u>www.NAMICertification.com</u> to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

| COMPANY NAME AND ADDRESS | | PRODUCT DESC | CRIPTION |
|--------------------------|-------------------------------------|---|------------------|
| Great Lakes Window | Series "ComfortSmart 3 Lite Slider" | | |
| 30499 Tracy Road | Vinyl Horizontal Sliding Window | | |
| Walbridge, OH 43465 | | | |
| | | Configuration: Glazing: Insulating Gla | |
| | Frame: | W-2756mm(108.5") | H-1591mm(62.63") |
| | Panel: | W-1327mm(52.25") | H-1484mm(58.43") |
| | DLO: | W-1246mm(49.06") | H-1405mm(55.31") |

| SPECIFICATION | PRODUCT RATING |
|--|---|
| AAMA/WDMA/CSA 101/I.S.2/A440-11 AAMA/WDMA/CSA 101/I.S.2/A440-08 AAMA/WDMA/CSA 101/I.S.2/A440-05 CSA A440S1-09 | Class R-PG20 2756 x 1591 (109 x 63)-HS HS-R20 2756 x 1591 (109 x 63) Design Pressure: 960 Pa (20 psf) Negative Design Pressure: 960 Pa (20 psf) Water Penetration Resistance Test Pressure: 290 Pa (6.06 psf) Canadian Air Infiltration/Exfiltration Level: A2 |

Product Tested By: Report No: Expiration Date: National Certified Testing Laboratories NCTL-110-19163-1/NCTL-110-18422-1/W-1874 July 31, 2026

Sh

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124

Email: nami@namiinc.com