NOTICE OF PRODUCT CERTIFICATION

| ATOS ACCREDITED AR | | |
|--------------------|-------------------------------|-----------------------|
| RE BILL | CERTIFICATION NO: | <u>NI013023.03-R3</u> |
| | DATE: | 02/23/2016 |
| | CERTIFICATION PROGRAM: | Structural |
| ATA STATE | COMPANY: | Atrium |
| CERT IN OUCT | CODE: | 1373-1 |
| TFIED PROU | REVISION DATE: | 03/06/2023 |

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | | PRODUCT DESC | CRIPTION |
|--------------------------|--|------------------|-----------------|
| Atrium Companies, Inc. | Series "705/755" | | |
| 9001 Ambassador Row | Vinyl Awning Window | | |
| Dallas, TX 75247 | w/Finless Installation | | |
| | Configuration: X Glazing: Insulating Glass (Annealed) | | |
| | Frame: | W-1219mm(48") | H-914mm(36") |
| | Vent: | W-1172mm(46.19") | H-865mm(34.09") |
| | DLO: | W-1060mm(41.75") | H-756mm(29.75") |

| SPECIFICATION | PRODUCT RATING |
|---------------------------------|---|
| AAMA/WDMA/CSA 101/I.S.2/A440-17 | Class LC-PG35 1219 x 914 (48 x 36)-AP |
| AAMA/WDMA/CSA 101/I.S.2/A440-11 | Design Pressure: ±1676 Pa (35 psf) |
| AAMA/WDMA/CSA 101/I.S.2/A440-08 | Water Penetration Resistance Test Pressure: 440 Pa (9.19 psf) |

Product Tested By: Report No: Expiration Date: Architectural Testing, Inc. E1448.01-801-47/W-2009 October 31, 2027

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 Email: nami@namiinc.com