# NOTICE OF PRODUCT CERTIFICATION

| | |
|---|---|
| **CERTIFICATION NO:** | **NI013674-R3** |
| **DATE:** | **04/03/2017** |
| **CERTIFICATION PROGRAM:** | **Structural** |
| **COMPANY:** | **Comfort View** |
| **CODE:** | **2111-1** |
| **REVISION DATE:** | **04/01/2026** |

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION |
|---|---|
| **Comfort View Products, LLC**<br>**320 Coweta Industrial Park**<br>**Building 7, Suite C-1**<br>**Newnan, GA 30265** | **Series "901/951"**<br>**Vinyl Fixed Window**<br>Configuration: O<br>Glazing: Insulating Glass (Annealed)<br>Frame: W-1829mm(72") H-1829mm(72")<br>DLO: W-1702mm(67") H-1702mm(67") |

| SPECIFICATION | PRODUCT RATING |
|---|---|
| **AAMA/WDMA/CSA 101/I.S.2/A440-11**<br>**AAMA/WDMA/CSA 101/I.S.2/A440-08**<br>**AAMA/WDMA/CSA 101/I.S.2/A440-05** | **Class CW-PG40 1829 x 1829 (72 x 72)-FW**<br>**FW-C40 1829 x 1829 (72 x 72)**<br>**Design Pressure: ±1920 Pa (40 psf)**<br>**Positive Design Pressure: 1920 Pa (40 psf)**<br>**Negative Design Pressure: 2160 Pa (45 psf)**<br>**Water Penetration Resistance Test Pressure: 580 Pa (12.11 psf)** |

Product Tested By: Architectural Testing, Inc.
Report No: E8069.02-501-47
Expiration Date: **May 31, 2036**

Administrator's Signature: _____


**NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.**
**4794 George Washington Memorial Highway**
**Hayes, VA 23072**
**Tel: (804) 684-5124**
**Email: nami@namiinc.com**