## **NOTICE OF PRODUCT CERTIFICATION**

TED CERTIFICATIO		
STAN ACCREDITA	<b>CERTIFICATION NO:</b>	<u>NI013716.09-R1</u>
A LE A	DATE:	<u>08/13/2019</u>
	<b>CERTIFICATION PROGRAM:</b>	<b>Structural</b>
	COMPANY:	<u>Nan Ya</u>
TAT GENERAT INSTIT	CODE:	<u>661-1</u>
CERTIFIED BRODUC	<b>REVISION DATE:</b>	<u>08/31/2022</u>
TED PRO		

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	<b>PRODUCT DESCRIPTION</b>	
Nan Ya Plastics Corporation USA	Series "SLPS" Glazed Fiberglass	
8989 North Loop East, Suite 800	<b>Inswing Patio Door Assembly</b>	
Houston, TX 77029	w/Standard or Mini-Blind Glazing	
	Configuration: OXX/O Glazing: IG-1/8" Tempered Glass/1/8" Annealed Glass/0.090" SentryGlas PVB Interlayer/1/8" Annealed Glass	
	Frame: W-3720mm(146.44") H-2500mm(98.44")	
	Panel: W-908mm(35.75") H-2419mm(95.25")	
	DLO: W-635mm(25") H-2007mm(79")	

SPECIFICATION	PRODUCT RATING
AAMA/WDMA/CSA 101/I.S.2/A440-11 CSA A440S1-17 ASTM E1886-05 ASTM E1996-05/09	Class LC-PG30 3720 x2500 (146 x 98)-SHD Design Pressure: ±1436 Pa (30 psf) Positive Design Pressure: 2400 Pa (50 psf) Negative Design Pressure: 2400 Pa (50 psf) Water Penetration Resistance Test Pressure: 223 Pa (4.65 psf) Canadian Air Infiltration/Exfiltration Level: A3 Wind Zone 4 - Missile Level D

Product Tested By: Report No: Expiration Date:

National Certified Testing Laboratories NCTL-210-4149-01/NCTL-210-4103-04 July 31, 2031

Shi

Administrator's Signature:

## NATIONAL ACCREDITATION AND **MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com