

# NOTICE OF PRODUCT CERTIFICATION



**Company:** BMC Millwork  
105 Broughton Street  
Ailey, GA 30410

**Certification No.:** NI014387-R1  
**Certification Date:** 04/16/2019  
**Expiration Date:** 04/30/2026  
**Revision Date:** 07/20/2023

**Product:** Fiberglass Glazed Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites (w/Wood Frame or Worldwide Composite Frame<sup>4</sup> unless noted)

**Specification:** TAS 202-94/ASTM E330-02

**Glazing:** Insulating Glass (Tempered) Full-Lite Doors Require "HPC" Construction Slabs

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 6'8"	+50/-50	0.0 psf	No	ATLNC 0207.01-17/ATLNC 1012.01-16R Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
X Single	O/S	Glazed	3'0" x 6'8"	+50/-50	3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup> 7.5 psf <sup>6</sup>	No	ATLNC 0207.01-17/ATLNC 1012.01-16R/W-1813/ W-1843/W-1860 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
XX Double	I/S	Glazed	6'0" x 6'8"	+50/-50	0 psf	No	ATLNC 0207.01-17/ATLNC 1012.01-16R Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
XX Double	O/S	Glazed	6'0" x 6'8"	+50/-50	3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> /8.25 psf <sup>5</sup>	No	ATLNC 0207.01-17/ATLNC 1012.01-16R/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
XO/OX Single w/Sidelite	I/S	Glazed	6'0" x 6'8"	+50/-50	0 psf	Door-No Sidelite-No	ATLNC 0207.01-17/ATLNC 1012.01-16R Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
XO/OX Single w/Sidelite	O/S	Glazed	6'0" x 6'8"	+50/-50	3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup>	Door-No Sidelite-No	ATLNC 0207.01-17/ATLNC 1012.01-16R/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
OXO Single w/Sidelites	I/S	Glazed	9'0" x 6'8"	+50/-50	0 psf	Door-No Sidelites-No	ATLNC 0207.01-17/ATLNC 1012.01-16R Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
OXO Single w/Sidelites	O/S	Glazed	9'0" x 6'8"	+50/-50	3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup>	Door-No Sidelites-No	ATLNC 0207.01-17/ATLNC 1012.01-16R/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
OXXO Double w/Sidelites	I/S	Glazed	12'4" x 6'8"	+50/-50	0 psf	Door-No Sidelites-No	ATLNC 0207.01-17/ATLNC 1012.01-16R Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17
OXXO Double w/Sidelites	O/S	Glazed	12'4" x 6'8"	+50/-50	3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> /8.25 psf <sup>5</sup>	Door-No Sidelites-No	ATLNC 0207.01-17/ATLNC 1012.01-16R/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0191-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-W-1815 5-Worldwide Pro T4 Threshold 6-Denotes HP Outswing Threshold

**National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072**

**Tel: (804) 684-5124/Fax: (804) 684-5122**

**NAMI AUTHORIZED SIGNATURE:** \_\_\_\_\_

A handwritten signature in black ink, appearing to be 'S.M.D.', is written over a horizontal line.