

NOTICE OF PRODUCT CERTIFICATION



Company: BMC Millwork
105 Broughton Street
Ailey, GA 30410

Certification No.: NI014387.07-R1
Certification Date: 04/16/2019
Expiration Date: 04/30/2026
Revision Date: 07/20/2023

Product: Fiberglass Opaque Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites (w/Wood Frame or Worldwide Composite Frame⁴ unless noted)

Specification: TAS 202-94/ASTM E330-02/ASTM E1886-05/ASTM E1996-09

Impact: Wind Zone 4-Missile Level D Non-Impact Glazing: Insulating Glass (Tempered)

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Opaque	3'0" x 6'8"	+60/-65	0.0 psf	Yes	NCTL-210-3835-1/W-1812 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
X Single	O/S	Opaque	3'0" x 6'8"	+60/-60	3.75 psf ¹ /6.0 psf ² 8.25 psf ³ /9.0 psf ⁵ 7.5 psf ⁶	Yes	NCTL-210-3835-1/W-1812/W-1813/W-1843/W-1860 Maximum Panel Size: 3'0" x 6'8" Anchor Details-MA-FL0187-17
XX Double	I/S	Opaque	6'0" x 6'8"	+50/-50	0 psf	Yes	ATLNC 0831.01-16/ATLNC 0901.02-16 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
XX Double	O/S	Opaque	6'0" x 6'8"	+50/-50	3.75 psf ¹ /6.0 psf ² 8.25 psf ³ /8.25 psf ⁵	Yes	ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
XO/OX Single w/Sidelite	I/S	Opaque Door Glazed Sidelite	6'0" x 6'8"	+50/-50	0 psf	Door-Yes Sidelite-No	ATLNC 0831.01-16/ATLNC 0901.02-16 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
XO/OX Single w/Sidelite	O/S	Opaque Door Glazed Sidelite	6'0" x 6'8"	+50/-50	3.75 psf ¹ /6.0 psf ² 8.25 psf ³ /9.0 psf ⁵	Door-Yes Sidelite-No	ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
OXO Single w/Sidelites	I/S	Opaque Door Glazed Sidelite	9'0" x 6'8"	+50/-50	0 psf	Door-Yes Sidelites-No	ATLNC 0831.01-16/ATLNC 0901.02-16 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
OXO Single w/Sidelites	O/S	Opaque Door Glazed Sidelite	9'0" x 6'8"	+50/-50	3.75 psf ¹ /6.0 psf ² 8.25 psf ³ /9.0 psf ⁵	Door-Yes Sidelites-No	ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
OXXO Double w/Sidelites	I/S	Opaque Door Glazed Sidelite	12'4" x 6'8"	+50/-50	0 psf	Door-Yes Sidelites-No	ATLNC 0831.01-16/ATLNC 0901.02-16 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
OXXO Double w/Sidelites	O/S	Opaque Door Glazed Sidelite	12'4" x 6'8"	+50/-50	3.75 psf ¹ /6.0 psf ² 8.25 psf ³ /8.25 psf ⁵	Door-Yes Sidelites-No	ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-W-1815 5-Worldwide Pro T4 Threshold 6-Denotes HP Outswing Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____